

FIG. 2





FIG. 3



SPECIFICATION

Method of and apparatus for supplying coating agent to coating robot

- 5 The present invention relates to a method of and an apparatus for supplying a coating agent such as a sealant to a coating robot such as a sealing robot which applies the coating agent to required portions of an article conveyed on a conveyor line. 5

During assembly of various articles such as automotive bodies, for example, many portions or areas of such articles have to be sealed to make airtight and liquidtight the mating edges of panels which are joined together as by spot welding. Sealing the innermost area of an engine compartment, in particular, has resulted in various problems. The process of sealing that area is complex, but the area has to be sealed quickly. The manual sealing procedure is subject to limitations. 10

In view of the above drawbacks, there has recently been proposed a sealing robot disposed on a conveyor line and having a sealing gun for automatically carrying out a sealing process, the sealing robot being operable for sealing an article according to a working program (see Japanese Laid-Open Patent Publication No. 55-81759 published June 20, 1980). 15

The sealing robot is supplied with a sealant by a fixed-displacement sealant supply pump during the sealing process. In the event that the outlet side of the pump fails to discharge the sealant due for example to a clog, an undue pressure buildup is developed in the pipe connected to the pump outlet, and hence the pump and pipes and devices coupled thereto may be damaged. If the inlet side of the pump fails to deliver the sealant to the pump, the pump operates idly and may be damaged. Should the pipes remain pressurized after a sealing procedure has been completed, the sealant in the pipes would be solidified. To prevent this, the pipes should be relieved of any remaining pressure subsequent to the sealing process. 20 25

Another problem with the conventional sealing robot is that when the sealing robot is to be slowed down to change its direction of movement during a sealing operation or when the rate of discharge of the sealant from the pump is varied due to aging of the viscosity of the sealant, the amount of the sealant coated on the article per unit distance that the sealing robot has traversed is also varied, with the result that the sealant coat on the article becomes irregular. This problem manifests itself and should be solved especially when sealing the joined edges (joined lines) of panels which define an automotive engine compartment inasmuch as the joined edges are curved and the sealing robot moves at largely different speeds along the joined edges. 30

35 The present invention has been made in view of the aforesaid problems. 35

According to the present invention, there is provided an apparatus for supplying a coating agent to a coating robot, comprising a coating robot, a supply source of a coating agent, a supply line for supplying the coating agent in a direction from the supply source to the coating robot, the supply line including a supply pipe, a coating agent supply pump on the supply line, first and second pressure sensors disposed downstream and upstream, respectively, of the coating agent supply pump with respect to said direction, for detecting pressures in the supply pipe, branch lines extending from the supply line downstream of the first pressure sensor and upstream of the second pressure sensor, respectively, relief valves on the branch lines, respectively, the relief valves having respective actuators, a pump driving device for driving the coating agent supply pump, and control means disposed between the first and second pressure sensors, and the actuators and the pump driving device for controlling the pump driving device and the actuators to stop operation of the coating agent supply pump and to open the relieve valves when the pressure detected by either one of the first and second pressure sensors falls outside of a prescribed pressure range. 40 45

According to the present invention, there is also provided a method of supplying a coating agent to a coating robot, comprising the steps of detecting pressures in a supply pipe downstream and upstream of a coating agent supply pump on a coating agent supply line extending from a supply source of a coating agent to a coating robot, releasing the pressure from the supply pipe through branch lines extending from the supply line downstream and upstream of the coating agent supply pump when the pressure in the supply pipe downstream or upstream of the coating agent supply pump falls outside of a prescribed pressure range, and stopping operation of the coating agent supply pump. 50 55

If the pressure in the supply line excessively rises or drops, then the relief valves are opened to release the pressure from the supply line and the supply pump is inactivated for thereby protecting the pipes, devices, and pump on the supply line from damage. 60

The coating robot has a coating applicator movable with respect to an article to which the coating agent is to be applied by the coating robot. The control means controls the pump driving device to vary the rate at which the coating agent is discharged from the pump as a function of the speed of relative movement of the coating applicator with respect to the article.

irrespective of the speed of relative movement of the coating applicator with respect to the article, so that the sealed area of the article has a neat appearance and is made highly airtight and liquidtight.

The above and further objects, details and advantages of the present invention will become
5 apparent from the following detailed description of a preferred embodiment thereof, when read
in conjunction with the accompanying drawings.

Figure 1 is a schematic diagram of an overall coating agent supply system for supplying a
coating agent to a coating robot, the coating agent supply system including an apparatus
according to the present invention;

10 *Figure 2* is a block diagram of an electric control circuit for controlling a motor driver and
solenoid drivers; and

Figure 3 is a diagram showing a control arrangement for controlling a motor which operates a
pump in the coating agent supply system.

The principles of the present invention will hereinafter be described by way of illustrative
15 example as being incorporated in a sealant supply system for supplying a sealant to a sealing
robot.

As shown in Fig. 1, a sealant applicator gun 3 having a sealant ejecting nozzle 2 is mounted
on the distal end of an arm 1a of a sealing robot 1. The sealant applicator gun 3 can be opened
and closed to supply and cut off a sealant from the nozzle 2.

20 A sealant supply line has a sealant storage tank 4 and a main pump 5 for pumping up a
sealant from the sealant storage tank 4. The sealant pumped up by the main pump 5 is
delivered through a main line 6 to individual lines 7 (only one shown) associated with respective
sealing robots. The line 7 is coupled to a selector valve 8 disposed upstream thereof and a line
shutoff valve 9 disposed downstream thereof. The line shutoff valve 9 is connected to a filter
25 10 positioned downstream thereof and coupled to a regulator 11 positioned downstream
thereof. The regulator 11 is connected to a pump 12 disposed downstream thereof for supply-
ing a fixed amount of a sealant, the pump 12 being operable by a motor 13 through a speed
reducer 14.

A high-pressure sensor 15 is disposed in the pipe of the line 7 downstream of the pump 12
30 for detecting a pressure higher than a prescribed pressure level in the line pipe. A high/low-
pressure sensor 16 is disposed in the pipe of the line 7 upstream of the pump 12 for detecting
a pressure higher than a prescribed higher pressure level in the line pipe and a pressure lower
than a prescribed lower pressure level in the line pipe. The high-pressure sensor 15 is coupled
through a downstream pipe 17 to the sealant applicator gun 3 of the sealing robot 1 for
35 supplying the sealant to the nozzle 2. A pressure relief passage 18 is branched from the line 7
upstream of the pipe 17 and downstream of the high-pressure sensor 15, the passage 18 having
a relief valve 19. The relief valve 19 can be opened and closed by an actuator 20, the relief
valve 19 being normally closed. A check valve 21 is disposed downstream of the relief valve 19
and coupled through a selector valve 22 to a return line 23 connected to the tank 4. Between
40 the regulator 11 and the high/low-pressure sensor 16, there is connected a pressure relief
passage 24 branched from the line 7 and having a relief valve 25 which can be opened and
closed by an actuator 26. A check valve 27 is disposed downstream of the relief valve 25 and
coupled to the return line 23 via the selector valve 22.

The actuators 20, 26 for the relief valves 19, 25 and an actuator 28 for operating the shutoff
45 valve 9 are coupled to a solenoid-operated valve 30 through an air pressure passage 29a. The
sealant applicator gun 3 is openable and closable by a solenoid-operated valve 31 coupled
thereto through an air pressure passage 29b. The solenoid-operated valves 30, 31 are coupled
to an air pressure source 32. When the solenoid-operated valve 30 is in a position A (as shown
in Fig. 1), the air pressure from the air pressure source 32 causes the actuators 20, 26, 28 to
50 keep the relief valves 19, 25 closed and also to keep the shutoff valve 9 open. Conversely,
when the solenoid-operated valve 30 is in a position B, the air pressure from the air pressure
source 32 causes the actuators 20, 26, 28 to keep the relief valves 19, 25 open and also to
keep the shutoff valve 9 closed. The solenoid-operated valve 30 is normally in the position A
against the spring bias with its solenoid energized when the power supply switch of the system
55 shown in Fig. 1 is turned on.

The sealant stored in the tank 4 is delivered through the lines 6, 7, the filter 10, and the
regulator 11 to the pump 12, and then pressurized by the pump 12 and supplied through the
pipe 17 to the sealant robot 1. The sealant supplied to the sealant robot 1 is fed through the
applicator gun 3 and ejected from the nozzle 2 toward an article to be sealed.

60 If the sealant pressure in the line 7 undergoes a change as detected by the pressure sensors
15, 16, then the motor 13 for operating the pump 12 and the actuators 20, 26 for the relief
valves 19, 25 are controlled as follows:

The output signal from the high-pressure sensor 15, which indicates the pressure in the line 7

pump 12 is higher than the prescribed pressure level due to a clog in the nozzle 2, for example, the comparator 33 applies a signal to a motor driver 34 to de-energize the motor 13, stopping the operation of the pump 12. At the same time, the output signal from the comparator 33 is sent to a solenoid driver 35 for thereby shifting the solenoid-operated valve 30 from the position A to the position B. Therefore, the actuator 20 opens the relief valve 19 to relieve the line 7 through the relief passage 18.

The output signal from the high/low-pressure sensor 16, which indicates the pressure in the line 7 upstream of the pump 12, is compared with reference signals indicative of prescribed higher and lower pressure levels by a comparator 36 shown in Fig. 2. When the pressure upstream of the pump 12 is higher than the higher pressure level, the comparator 36 applies a signal to the motor driver 34 to de-energize the motor 13 to stop the operation of the pump 12. The comparator 36 also applies its signal to a solenoid driver 37 to shift the solenoid-operated valve 31 from the position A to the position B, whereupon the relief valve 25 is opened by the actuator 26 to relieve the pipe 7 through the relief passage 24.

When the pressure upstream of the pump 12 is lower than the lower pressure level because of a sealant shortage, for example, the comparator 36 issues a signal to the motor driver 34 to turn off the motor 13, thus preventing the motor 13 from idly rotating. Simultaneously, the relief valve 25 is opened by the actuator 26.

When the sealant supply system stops its operation, the power supply switch is turned off to deenergize the solenoid of the solenoid-operated valve 30, which is then shifted to the position B under the spring bias. Thus, the relief valves 19, 25 are opened to release the pressure from the line 7 for thereby preventing the sealant from being solidified in the line 7.

As described above, in the event of an undue pressure buildup or drop due to a clog or a sealant shortage, for example, the line 7 and the pump 12 are protected against damage or breakage because the pressure in the line 7 is released and the pump 12 is stopped in its operation at the same time. Upon shutdown of the entire system, the sealant is prevented from being solidified in the line 7 since the pressure in the line 7 is released.

Fig. 3 schematically shows a control arrangement for controlling the rotational speed of a sealant supply pump with controller. Those parts which correspond to those shown in Fig. 1 are denoted by corresponding reference characters with the addition of "100".

A sealant is supplied through a main pipe 106. A gear pump 112 has an inlet port connected to the main pipe 106 through a branch pipe 107 and an outlet port coupled via a joint pipe 117 to a sealant applicator gun 103 mounted on a sealing robot 101, the branch pipe 107 having a valve 108.

The gear pump 112 has its rotatable shaft coupled to a servomotor 113 through a speed reducer 114. The gear pump 112 is operated by the servomotor 113 to discharge a constant amount of sealant per revolution of the rotatable shaft of the gear pump 112. The servomotor 113 is electrically connected to a motor controller 50 which controls energization of the servomotor 113.

The sealing robot 101 has an arm 101a on which the applicator gun 103 is supported. The sealing robot 101 is electrically connected to a robot controller 60, and is controllable by the robot controller 60 to move the applicator gun 103 with respect to an article 70 such as an automobile panel. More specifically, the sealing robot 101 is controlled by a robot control signal from the robot controller 60 to swing the arm 101a for moving the applicator gun 103 along an article area to which the sealant is to be applied.

The robot controller 60 is electrically coupled to the motor controller 50 for applying the robot control signal also to the motor controller 50. The motor controller 50 determines the speed of rotation of the servomotor 113 based on the robot control signal supplied from the robot controller 60.

The sealant may be coated on the article by the applicator gun 103 either when the sealant is ejected from the applicator gun 103 that is positioned closely to the article 70 or when the sealant is ejected from the applicator gun 103 that is spaced a certain distance from the article 70.

The system shown in Fig. 3 operates as follows: The robot controller 60 controls the sealing robot 101 to move the applicator gun 113 relatively to the article 70, and also supplies the motor controller 50 with a robot control signal which represents the speed of relative movement of the applicator gun 113 with respect to the article 70. The motor controller 50 responds to the robot control signal from the robot controller 60 to control the servomotor 113 to keep the rotational speed of the servomotor 113 in proportion to the speed of relative movement of the applicator gun 103 with respect to the article 70. Therefore, the rate at which the sealant is discharged by the gear pump 112, i. e., the rate at which the sealant is applied by the applicator gun 103 to the article 70, varies proportionally to the speed of relative movement of the applicator gun 103 with respect to the article 70. As a result, the amount of the sealant applied to the article 70 per unit area that is coated with the sealant remains constant irrespective of

area of the article 70 which is sealed by the applied sealant is therefore well sealed without the danger of losing the airtight and liquidtight structure or a neat appearance, which would otherwise be damaged by a sealant shortage. The reference rate of applying the sealant can be determined by setting a reference rotational speed for the servomotor 113 when teaching the sealing robot 101 a path of travel (coating path) of the applicator gun 103.

An experiment conducted by the inventors indicated that when the reference rate of applying the sealant was set to 25 cc/m and the gear pump 112 having a discharging capability of 4.7 cc/rev. and the speed reducer 114 having a speed reduction ratio of 1/11 were used, the rate of application of the sealant could be uniformly kept at the reference rate by controlling the rotational speed of the servomotor 113 as shown in the following table:

| Speed of gun 103 (m/min) | Rate of discharge from gear pump 112 (cc/min) | Rotational speed of gear pump 112 (r.p.m.) | Rotational speed of servomotor 113 (r.p.m.) |
|--------------------------|---|--|---|
| 20 | 500 | 106.4 | 1170.4 |
| 15 | 375 | 79.8 | 877.8 |
| 10 | 250 | 53.2 | 585.2 |
| 5 | 125 | 26.6 | 292.6 |

While the stepwise control is shown in the above example by controlling the rotational speed of the servomotor 113 at discrete levels, the rotational speed of the servomotor 113 may also be controlled continuously. The speed of travel of the applicator gun 103 may be detected directly by some suitable detector, rather than through the control signal from the robot controller 60.

The control system shown in Fig. 3 may be used in combination with or independently of the control system illustrated in Fig. 2.

The invention has been shown and described as being applied to an apparatus for supplying a sealant to an article such as an automobile body. However, the principles of the present invention may find various other uses such as an apparatus for supplying a paint, an adhesive, or any of various other mediums having a certain viscosity to an coating or applicator robot.

Although there has been described what is at present considered to be the preferred embodiment of the present invention, it will be understood that the invention may be embodied in other specific forms without departing from the spirit or essential characteristics thereof. The present embodiment is therefore to be considered in all aspects as illustrative, and not restrictive. The scope of the invention is indicated by the appended claims rather than by the foregoing description.

CLAIMS

1. An apparatus for supplying a coating agent to a coating robot, comprising:
 - a coating robot;
 - a supply source of a coating agent;
 - a supply line for supplying the coating agent in a direction from said supply source to said coating robot, said supply line including a supply pipe;
 - a coating agent supply pump on said supply line;
 - first and second pressure sensors disposed downstream and upstream, respectively, of said coating agent supply pump with respect to said direction, for detecting pressures in said supply pipe;
 - branch lines extending from said supply line downstream of said first pressure sensor and upstream of said second pressure sensor, respectively;
 - relief valves on said branch lines, respectively, said relief valves having respective actuators;
 - a pump driving device for driving said coating agent supply pump; and
 - control means disposed between said first and second pressure sensors, and said actuators and said pump driving device for controlling said pump driving device and said actuators to stop operation of said coating agent supply pump and to open said relieve valves when the pressure detected by either one of said first and second pressure sensors falls outside of a prescribed pressure range.
2. An apparatus according to claim 1, wherein said first pressure sensor detects pressures

sure higher and lower than said prescribed pressure range.

4. An apparatus according to claim 1, wherein said actuators are arranged to normally keep the respective relief valves closed and to open the respective relief valves when a power supply switch of said supply source is turned off.

5 5. An apparatus according to claim 1, wherein said coating robot has a coating applicator movable with respect to an article to which the coating agent is to be applied by the coating robot, said control means being arranged to control said pump driving device for varying the rate at which the coating agent is discharged from said pump as a function of the speed of relative movement of said coating applicator with respect to said article. 5

10 6. An apparatus according to claim 5, further including robot controller means for controlling movement of said coating applicator with respect to said article, said robot controller means being arranged to apply a signal indicative of said speed to said control means, said control means being arranged to control said pump driving device for controlling said rate according to said signal. 10

15 7. A apparatus for supplying a coating agent to a coating robot, comprising: 15
a coating robot, said coating robot having a coating applicator movable with respect to an article to which a coating agent is to be applied by the coating robot;

a supply source of a coating agent;
a supply line for supplying the coating agent from said supply source to said coating robot;
20 a coating agent supply pump on said supply line; 20
a pump driving device for driving said coating agent supply pump; and
control means for controlling said pump driving device to vary the rate at which the coating agent is discharged from said pump as a function of the speed of relative movement of said coating applicator with respect to said article.

25 8. An apparatus according to claim 7, further including robot controller means for controlling movement of said coating applicator with respect to said article, said robot controller means being arranged to apply a signal indicative of said speed to said control means, said control means being arranged to control said pump driving device for controlling said rate according to said signal. 25

30 9. An apparatus for supplying a coating agent to a coating robot, comprising: 30
a coating robot;

a supply source of a coating agent;
a supply line for supplying the coating agent in a direction from said supply source to said coating robot, said supply line including a supply pipe;
35 a coating agent supply pump on said supply line; 35

a pressure sensor disposed in one of positions which are located downstream and upstream, respectively, of said coating agent supply pump with respect to said direction, for detecting a pressure in said supply pipe;

40 branch lines extending from said supply line downstream of said first pressure sensor and upstream of said second pressure sensor, respectively; 40

relief valves on said branch lines, respectively, said relief valves being operable when the pressure in said supply pipe falls outside of a predetermined pressure range;

a pump driving device for driving said coating agent supply pump; and
45 control means disposed between said pressure sensor and said pump driving device for controlling said pump driving device to stop operation of said coating agent supply pump when the pressure in said supply pipe detected by said pressure sensor falls outside of said prescribed pressure range. 45

10. A method of supplying a coating agent to a coating robot, comprising the steps of:
detecting pressures in a supply pipe downstream and upstream of a coating agent supply
50 pump on a coating agent supply line extending from a supply source of a coating agent to a coating robot; 50

releasing the pressure from said supply pipe through branch lines extending from the supply line downstream and upstream of said coating agent supply pump when the pressure in the supply pipe downstream or upstream of said coating agent supply pump falls outside of a
55 prescribed pressure range; and 55
stopping operation of said coating agent supply pump.

11. A method according to claim 10, wherein pressures in said supply pipe higher than a prescribed pressure level are detected downstream of said coating agent supply pump.

12. A method according to claim 10, wherein pressures in said supply pipe higher and lower
60 than the prescribed pressure range are detected upstream of said coating agent supply pump. 60

13. A method according to claim 10, wherein the pressure in said supply pipe is released when said coating agent supply line is shut off.

14. A method according to claim 10, wherein said coating robot has a coating applicator movable with respect to an article to which the coating agent is to be applied, the rate at which

of the speed of relative movement of said coating applicator with respect to said article when said coating agent supply pump is in operation.

15. A method of supplying a coating agent to a coating robot, comprising the steps of:
detecting a pressure in a supply pipe downstream or upstream of a coating agent supply
5 pump on a coating agent supply line extending from a supply source of a coating agent to a coating robot; 5
releasing the pressure from said supply pipe through branch lines extending from the supply line downstream and upstream of said coating agent supply pump when the detected pressure falls outside of a prescribed pressure range; and
10 10 stopping operation of said coating agent supply pump. 10
16. Apparatus for supplying a coating agent substantially as hereinbefore described with reference to the accompanying drawings.
17. A method of supplying a coating agent substantially as hereinbefore described.

THIS PAGE BLANK (USPTO)